

USB Ultra Schnell-Reiselerader „GaNto35“ USB-A + USB-Type-C® | 35 Watt GaN Technologie




Art.Nr: 263699



Art.Nr: 263705



Ultra Fast Charger



100-240V AC
Input



Total Power



USB Type-C PD
USB-A FC



Charge two devices



Safe & Protected

Produkt Info



Kompakter, leistungsstarker Schnell-Reiselerader mit USB-A und USB-Type-C Anschluss zum schnellen Aufladen von allen USB kompatiblen Geräten. Der Type-C Anschluss ist mit **Power Delivery** Technologie ausgestattet und liefert bis zu **35 Watt**. Der USB-A Anschluss liefert bis zu **27 Watt** Leistung. Mit dem Reiselerader **GaNto35** können **zwei Geräte gleichzeitig** schnell und sicher aufgeladen werden. Der Strombedarf der angeschlossenen Geräte wird ermittelt und der verfügbare Strom entsprechend zugeteilt. Ihre Geräte sind durch die **Sicherheitsmechanismen** des **GaNto** bestens **geschützt**. Die wichtigste Eigenschaft der verwendeten **GaN** Technologie, ist die sehr geringe Wärmeenerzeugung. Dies ermöglicht eine sehr **kompakte Bauweise** mit einer **hohen Leistungsdichte** und **Leistungskapazität** entsprechend den **Sicherheitsstandards**.

Technische Daten:

- Eingangsspannung: 100-240V AC 50/60Hz 1.0A
- Ausgang Type-C: DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W, 12.0V/2.92A/35.0W, 15.0V/2.33A/35.0W, 20.0V/1.75A/35.0W
PPS: 3.3-16.0V/max.3.00A/35W
- Ausgang USB-A: DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W, 12.0V/2.25A/27.0W, 20.0V/1.35A/27.0W
- Ausgang Type-C + USB-A: 5.0V/3.0A/15.0W
- Gesamtleistung: 35.0 Watt
- Kompatible Schnellladetechnologien: Quick Charge 3.0, Power Delivery 3.0 (PPS), AFC, FCP, SCP
- Durchschnittliche Effizienz im Betrieb: ≥76.41%
- Effizienz bei geringer Last (10%): 81.05%
- Leistungsaufnahme bei Nulllast: ≤0.3W
- Abmessungen: 74.3 x 36 x 36 mm (inklusive AC-Stecker)
- Gewicht: 64g

Art.Nr: 263699

EAN: 4024559263699

Compact, powerful fast travel charger with USB-A and USB Type-C port for fast charging of all USB compatible devices. The Type-C port features **Power Delivery technology** and delivers up to **35 watts**. The USB-A port delivers up to **27 watts** of power. The **GaNto35** travel charger can be used to quickly and safely charge **two devices** at the same time.

The power requirements of the connected devices are determined and the available power is allocated accordingly. Your devices are well **protected** by the GaNto's **safety mechanisms**. The most important feature of the **GaN** technology used, is the very low heat generation. This allows a **very compact design** with a **high power density** and **power capacity** according to **safety standards**.

Technical data:

- Input voltage: 100-240V AC 50/60Hz 1.0A
- Output Type-C: DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W, 12.0V/2.92A/35.0W, 15.0V/2.33A/35.0W, 20.0V/1.75A/35.0W
PPS: 3.3-16.0V/max.3.00A/35W
- Output USB-A: DC 5.0V/3.0A/15.0W, 9.0V/3.0A/27.0W, 12.0V/2.25A/27.0W, 20.0V/1.35A/27.0W
- Output Type-C + USB-A: 5.0V/3.0A/15.0W
- Total power: 35.0 Watts
- Compatible fast charging technologies: Quick Charge 3.0, Power Delivery 3.0 (PPS), AFC, FCP, SCP
- Average efficiency during operation: ≥76.41%
- Efficiency at low load (10%): 81.05%
- Power consumption at no load: ≤0.3W
- Dimensions: 74.3 x 36 x 36 mm (include AC pin)
- Weight 64g

Art.Nr: 263705

EAN: 4024559263705